

FASTENERS FOR PANELS

Single snap-on fasteners

Recommended use:

These fasteners are mainly used to fix trim panels. They can also be used as temporary fastening. They are suitable for assemblies exposed to low mechanical stress.



SHAPES



P = PANEL THICKNESS	REFERENCE	B	A	e	SHAPE
0.7	C 3774 ZH	12	16.5	0.7	e
0.8 to 1.8	C 4741 ▲	12	8.5	0.4	c
1.5 to 2.5	SCO 6963 ZBJ	4	7	0.4	b
1.5 to 3	SCO 5790 ZBJ	12.7	15.7	0.6	b
1.6 to 2.4	C 3701 ▲	12	8.2	0.4	c
2 to 2.5	SCO 6933 ZB	4	7	0.4	b
2 to 2.5	SCO 7309 TRJ	20.2	16.1	0.5	c
2.5 to 3	C 3778 ZE	12	13	0.4	e
2.5 to 3	C 4782 DC	12	8.3	0.4	e
2.5 to 4	SCO 7352 SRJ	13	9.6	0.3	b
3 to 4	SCO 7041 YN	13	13	0.4	e
3.5 to 3.8	C 3765 DC	10	15	0.5	d
3.5 to 5	C 5132 DC	12	11	0.4	c
5.3 to 6.3	C 4792 DC	12	11	0.5	c
5.5 to 6.5	C 2775 ZH	12	11	0.4	c
6	C 2761 ZH	12	11	0.5	d

Recommended assembly method:

Fit the fastener manually by pushing it over the edge of the panel. On thick panels, a simple tool may be necessary.

FASTENER

MATERIAL	Treated spring steel
SURFACE	See table on cover flap
TREATMENT	Except for parts with reference "▲": Phosphating
COLOUR	See table on cover flap Except for parts with reference "▲": Black paint