


## FASTENERS FOR PANELS

### Double snap-on fasteners

#### Recommended use:

These fasteners are mainly used to join panels end to end. They provide an advantageous alternative to screwed fasteners. They are easy to dismantle and reuse.

#### SHAPES



a



b



c



d

P1 = PANEL THICKNESS	P2 = PANEL THICKNESS	REFERENCE	A	B	e	SHAPE VARIANT
0.7 to 2.5	0.7 to 2.5	SCO 6043 ZCJ	17.7	20	0.7	c
0.8 to 1.5	0.8 to 1.5	C 36562 ▲	13.2	13	0.5	a
0.8 to 2.3	0.8 to 2.3	C 8452 DK	10	12	0.4	b
1 to 1.5	1.8 to 2.5	SCO 5784 ▲	13	9	0.6	c
1.7 to 1.8	3.8	SCO 7216 ZGJ	16.6	15	0.6	c
1.8	2.4	SCO 7286B TGJ	11.6	15	0.6	b
2	2	C 5039A DK	14.6	12	0.6	b
2 to 3.2	0.6 to 0.8	C 46131 DD	9.4	12	0.5	d
2 to 3.2	1.9 to 2.3	C 46134 ▲	10	12	0.5	d
2 to 3	2.5	SCO 6714 ▲	19.5	15	0.5	b
2.3 to 2.7	0.8	C 2631 ZF	18	25	0.6	c
2.5	9	C 8266 DK	16	14	0.5	c



#### FASTENER

<b>MATERIAL</b>	Treated spring steel
<b>SURFACE</b>	See table on cover flap
<b>TREATMENT</b>	Except for parts with reference "▲": Phosphating
<b>COLOUR</b>	See table on cover flap Except for parts with reference "▲": Black paint

#### Recommended assembly method:



1. Position the fastener at the edge of the panel.
2. Fit the two pinching sections of the double fastener over the two panels using a simple tool.
3. Once correctly fitted in position the fastener is self-retaining.